

Vasi di espansione multifunzione per acqua calda sanitaria
Multifunction expansion vessels for hot potable water

EXTRAVAREM LC

-10 +99 °C



Codice <i>Item</i>	Capacità l. <i>Capacity (lts.)</i>	Press. Max <i>Max Pressure</i> (bar)	Raccordo <i>Connector</i>	Dimensioni <i>Dimensions</i>		Imballo Packaging <i>(volume m³)</i>	Quantità per Paletta <i>Quantity in std pallet</i>
				D	H		
R1 016 828	0,16*	15	1/2"	65	105	0,035	1480
R1 002 828	2*	10	1/2"	125	237	0,050	576
R1 005 228	5*	8	3/4"	160	325	0,020	210
R1 008 228	8	8	3/4"	200	337	0,031	144
R1 012 228	12	8	3/4"	270	300	0,024	72
R1 018 228	18	8	3/4"	270	422	0,034	56
R1 025 228	25	8	3/4"	290	465	0,041	63
R1 024 228	24	8	3/4"	351	338	0,044	54
R1 040 228	40	8	3/4"	320	560	0,080	36

Vasi di espansione a membrana fissa per acqua sanitaria calda e fredda, riscaldamento, bollitori, anti colpo d'ariete, elettropompe.

Flangia in acciaio inox; precarica 3,5 bar.

*Marchio CE non applicabile ai modelli da 0,16, 2 e 5 litri. Raccordo 1" su richiesta per i modelli da 24, 25 e 40 litri.

R1016828: 10 pezzi per scatola

R1002828: 6 pezzi per scatola

Fixed membrane expansion vessels for hot and cold potable water use, heating, boilers, water hammer arrester, pumps, water storage. Stainless steel flange; 3.5 bar precharge.

**CE mark not applicable on 0.16, 2 & 5 lts.*

1" connector upon request for 24, 25, 40 lts.

Models R1016828: 10 pieces in one cartonbox

R1002828: 6 pieces in one cartonbox

Vasi di espansione multifunzione / impianti di sollevamento acqua

Multifunction expansion vessels for hot potable water and booster system

MAXIVAREM LC

-10 +99 °C



Codice <i>Item</i>	Capacità l. <i>Capacity (lts.)</i>	Press. Max <i>Max Pressure</i> (bar)	Raccordo <i>Connector</i>	Dimensioni <i>Dimensions</i>		Imballo Packaging <i>(volume m³)</i>	Quantità per Paletta <i>Quantity in std pallet</i>
				D	H		
UC 060 367	60	10	1"	380	671	0,112	25
UC 080 367	80	10	1"	450	650	0,135	20
UC 100 367	100	10	1"	450	731	0,173	15
UC 150 467	150	10	1"1/2	554	808	0,265	8
UC 200 467	200	10	1"1/2	554	988	0,324	8
UC 250 467	250	10	1"1/2	624	1006	0,423	6
UC 300 467	300	10	1"1/2	624	1160	0,481	6
UC 400 467	400	10	1"1/2	624	1520	0,771	6

Membrana intercambiabile per acqua a uso alimentare.

Flangia in acciaio inox.

Precarica 2 bar.

Colore bianco su richiesta.

Replaceable membrane for hot potable water use. Stainless steel flange.

2 bar precharge.

White color on demand.